

SPECIFICATIONS FOR SPECIAL SERVICE 4x4
2007 Chevrolet Tahoe
2007 Ford Expedition

SSP7-2

Vehicles are required to be equipped with standard factory equipment unless dealer installation is permitted. Additionally, vehicles must comply with Federal Government regulations, and include, but not be limited to, the following bid requirements:

- Airbags:** Driver and passenger frontal impact air bag passive restraint system.
- Air Conditioning:** Required.
- Alternator:** Transistorized regulator, 150 amp minimum output capacity, minimum curb idle output of 45 amps (at manufacturer's recommended idle speed).
- Axles:** Heavy-duty 4x4, auto hubs.
- Body Side Molding:** Standard side molding.
- Brakes:** Power-assisted anti-lock brake system required. Four wheel disc preferred.
- Cold Climate Package:** (a) Heavy-duty battery with minimum of 650 cold cranking amps required. (b) Engine block heater.
- Color:** White exterior required. Dark blue or charcoal interior preferred, gray acceptable. Any trim to be color coordinated.
- Cooling System:** Maximum size available.
- Cruise Control:** Factory installed speed control required.
- Defroster/Heater:** (a) Hot water, fresh-air type (largest size). (b) Factory installed electrical grid type rear window defroster required.
- Differential:** Heavy-duty. 3.42 or 3.73 gear ratio.
- Doors:** Four-door model required. Rear lift-gate with lift glass required.
- Engine:** High performance V8 with fuel injection, minimum piston displacement of 5.3 liter.
- Floor Covering:** Black rubber/vinyl preferred.
- Headlights:** High and low beam quartz-halogen headlamps. If equipped with daytime running lights, design shall incorporate a means to turn the lights off at driver's discretion.
- Hood Latch Release:** Inside hood latch release.
- Horn:** Dual electric horns.
- Inspection:** Prior to acceptance of delivery to the State of North Dakota, dealer shall schedule a pilot inspection with a representative of the North Dakota Department of Transportation and a representative of the North Dakota Highway Patrol in order to determine compliance with specifications.
- Lights & Switches:** (a) Engine, glove box (if available) and rear cargo compartment lights. (b) Factory installed dome/map light. Prefer deletion of any overhead console. (c) No interior light to be automatically illuminated by open doors.
- Locks:** (a) Power door locks required (driver/front passenger operated). (b) Four keys to be furnished with each vehicle. Third and fourth keys may be dealer supplied on original equipment blank only. A different key is required for each vehicle. (c) Rear door handles required to be capable of being inoperative (acceptable to be inoperative by use of child safety lock switch).
- Mirrors:** (a) Interior rearview mirror with day/night capability. (b) Both left and right

- side exterior mirrors with interior remote control. (c) Heated mirror defroster feature.
- Radio:** Standard features including at least AM/FM/clock.
- Radio Noise Suppression:** If available, equipped with radio noise suppression package to include any optional grounding straps.
- Seats:** (a) Heavy-duty bucket front seats covered with heavy-duty cloth. Power driver's seat required. At least the driver's seat to have heavy-duty construction designed for rugged use and comfortable foam-padded seat cushions and backs. To permit installation of equipment, a minimum width of ten inches is required between the bucket seats. Deletion of center console between seats required. (b) Second row seat required; third row seat not allowed. Second row seat may have vinyl upholstery.
- Speedometer:** If available, calibration to within +/- 2 mph accuracy with factory certification and labeling.
- Steering:** Power steering.
- Steering Wheel:** Tilt type steering wheel.
- Suspension System:** Heavy-duty suspension with stability control system.
- Tires:** Tires (including spare) to be all-season radials with black sidewalls and a speed rating to meet or exceed vehicle performance capabilities. Spare to be mounted under vehicle.
- Tools:** Wheel wrench and jack.
- Tow Hooks:** Front tow hooks required.
- Transmission:** Four speed automatic.
- Wheelbase:** 116 inch minimum wheelbase allowed.
- Wheels & Covers:** Heavy-duty wheels, black in color with hubcaps preferred, full wheel covers acceptable. Full size spare required.
- Windows:** (a) Side windows to be electrically powered with active controls for driver and front passenger. Driver's door to have master lock switch for all windows. (b) All glass to be solar tinted with additional tinting for rear window and side windows behind the driver.
- Wiring Diagrams:** Two text or electronic copy of wiring diagrams/vehicle schematics requested which will be made available for use by equipment installers.
- Wipers:** Electric with multiple speed intermittent feature. Wiper required on rear lift-gate window.